

# Limited Edition Pink DATACARD® SD260™ CARD PRINTER SPECIFICATIONS



## SD260™ Printer Standard Features

**Print technology**  
Direct-to-card dye-sublimation/resin thermal transfer

**Print capabilities**  
One-sided, edge-to-edge printing  
Full-color and monochrome printing capability  
Alphanumeric text, logos and digitized signatures  
Variety of bar codes: 1D/2D bar code images  
Printer pooling/sharing (available soon)

**Print resolution**  
300 dots per inch, 256 shades per color panel

**Print quality**  
Ability to conform to sRGB standard  
Flexible color management options

**Print speed**  
Full-color printing: up to 200 cards per hour, single-sided (YMCKT\*)  
Monochrome printing: up to 830 cards per hour, one-sided (black HQ\*)

**Printer memory**  
128 MB standard

**Printer display**  
Printer status messages  
Multiple backlight settings  
International languages available: English, Spanish, German, Italian and Japanese

**Card capacity**  
Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard  
Front exception card slot

**Printer driver**  
Adjustable color controls with image preview  
Pre-set area to block printing on magnetic stripe, with escapes for custom areas  
Utilizes Windows® XPS-based technology for high-fidelity printing  
Secure disabling of card remake  
SDK for Windows operating system printer driver  
User interface languages available: English, Spanish, German, Italian, Japanese, Traditional Chinese, Portuguese, Korean and Arabic

**User-friendly operation**  
Printer messages display on LCD panel  
Graphical display on Windows 7 and Windows Vista® operating systems  
Easy, fast installation  
Card remake standard with cancel option  
Operator-replaceable printhead  
Front panel soft power button

**Datacard® Certified Supplies featuring Intelligent Supplies Technology™**  
Automatic identification and validation for ribbons  
Adjustable low ribbon and cleaning cycle alerts  
Ribbon saver

**Warranties**  
30-month standard depot warranty  
30-month printhead warranty (no pass restrictions)

## SD260 Printer Options

**Magnetic stripe encoding (field upgrades only)**  
ISO 7811 three-track option (high- and low-coercivity)  
JIS Type II single-track option  
Support for standard and custom data formats

**End-user upgradeable options**  
Kensington® security lock for printer

**Printer cleaning supplies**

**Print ribbon kits - color**  
Full-color with resin black and topcoat panel, YMCKT\*, 250 images  
Full-color with resin black and topcoat panel, YMCKT\*, 500 images  
Full-color short panel with resin black and topcoat panel, ymckT\*, 650 images  
Resin black and topcoat panel, KT\*, 1000 images

**Print ribbon kits - monochrome**  
Resin black HQ\* (high quality), 500 images  
Resin black HQ\* (high quality), dark blue, white, red, green, silver, gold, metallic silver, metallic gold, 1500 images  
New, improved scratch-off, 1500 images

## SD260 Printer Specifications

**Physical dimensions**  
L 15.4 in. x W 6.9 in. x H 8.8 in.  
(39.1 cm x 17.5 cm x 22.4 cm)

**Weight**  
8.1 lbs (3.7 kg) (depending on options)

**Electronic requirements**  
100/120V, 50/60 Hz  
220/240V, 50/60 Hz

**Plastic cards accepted**  
ISO ID-1/CR-80 size cards;  
3.370 in. x 2.125 in. (85.6 mm x 53.98 mm)  
PVC with glossy laminate surface  
Select key fob cards (ISO ID-1/CR-80 size cards)  
Datacard® StickiCard™ adhesive-backed plastic cards

**Card thickness accepted**  
0.010 in. to 0.037 in. (0.254 mm to 0.939 mm)

**Operating environment**  
60°F to 95°F (15°C to 35°C)  
20% to 80% non-condensing humidity

**Storage environment**  
5°F to 140°F (-15°C to 60°C)  
10% to 90%, non-condensing humidity

**Connectivity**  
Bidirectional USB 2.0 high speed  
Ethernet 10 Base-T/100-Base-TX (with activity light)

**Operating system support for printer driver**  
Windows 7 (32 and 64 bit)  
Windows Vista (32 and 64 bit)  
Windows Server® 2008 (64 bit)  
Windows XP SP3 (32 bit)  
Windows Server 2003 R2 (32 bit)  
Microsoft Windows Hardware Quality Labs (WHQL) certified



**Agency approvals**  
cULus, FCC, I.C., CE, Ctick, VCCI, RoHS, WEEE, ENERGY STAR®, CCC, KC

**Environment/energy-saving features**  
ENERGY STAR qualified printer  
Biodegradable supply cores made with EcoPure® additive  
Recyclable enclosure plastics (marked with recycle symbol per Resin Identification Code)  
Recyclable packaging

**Included with SD260 printer**  
Printer driver CD, Quick Install Guide and warranty  
Free ID Works® Intro identification software  
Cleaning pen  
Cleaning roller spindle  
USB cable  
Power supply  
Power cord (region-specific)



**Datacard Group**

### Corporate Headquarters

11111 Bren Road West  
Minnetonka, Minnesota 55343-9015  
Phone: +1 952 933 1223  
www.datacard.com  
info@datacard.com

\*Ribbon type and number of panels; Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Inline Topcoat, HQ=High Quality

Datacard, SD260, StickiCard, Intelligent Supplies Technology, and ID Works are trademarks, registered trademarks and/or service marks of DataCard Corporation in the United States and/or other countries. Windows, Windows Server and Windows Vista are registered trademarks of Microsoft Corporation. Kensington is a registered trademark of ACCO Brands Corporation. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency. EcoPure is a registered trademark owned by Bio-Tec Environmental LLC. Names and logos on cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental.

©2011 DataCard Corporation. All rights reserved. Specifications subject to change without notice.